

Cod. 00412062

VRLA BATTERY AGM TECHNOLOGY

Revision 4.0

Specifications

Nominal Voltage (V) 12V

Nominal Capacity

16 min rate	(144W to 9.60V)	36Wh
20 hour rate	(0.3A to 10.50V)	6Ah
10 hour rate	(0.57A to 10.50V)	5.7Ah
5 hour rate	(1.02A to 10.20V)	5.1Ah
1 C	(6A to 9.60V)	3.8Ah
3 C	(18A to 9.60V)	2.4Ah

Weight Approx. 1.93kg (4.25 Lbs.)

Internal Resistance (at 1KHz) Approx. 16 mΩ

Maximum Discharge Current for

5 seconds: 90A

Charging Methods at 25°C (77°F)

Cycle use:

Charging Voltage 14.4 to 15.0V

Coefficient -5.0mv/°C/cell

Maximum Charging Current: 1.8A

Standby use:

Float Charging Voltage 13.50 to 13.80V

Coefficient -3.0mv/°C/cell

Operating Temperature Range

Charge -15°C (5°F) to 40 °C (104°F)

Discharge -15°C (5°F) to 50 °C (122°F)

Storage -15°C (5°F) to 40 °C (104°F)

Charge Retention (shelf life) at 20°C (68°F)

1 month 92%

3 month 90%

6 month 80%


Case Material ABS UL94HB

(Option: ABS UL94 V-0 flame retardant)



Terminal F2 (Faston Tab 187 or 250)

ENERGY SAFE

Dimensions mm (inch)



F2 (FASTON TAB NO. 250)




Cod. 00412062


VRLA BATTERY AGM TECHNOLOGY

Revision 4.0


Effect of Temperature on Capacity 25°C(77°F)




Capacity Retention Characteristic



Trickle (or float) Service Life



Cycle Service Life



PERFORMANCE DATA

Discharge Rates in Watts to Various End Voltages at 25°C (77°F)

Time	End Voltage	1.85V	1.80V	1.75V	1.70V	1.67V	1.65V	1.60V
5	min	227	262	284	302	308	315	324
8	min	168	195	214	228	234	239	246
10	min	154	175	188	198	203	206	212
15	min	122	134	143	150	152	155	158
20	min	97.5	106	114	120	121	123	125
30	min	79.8	85.5	88.6	91.4	92.6	93.8	95.6
60	min	43.2	46.4	48.2	49.8	50.3	50.9	51.8
120	min	26.4	27.9	29.2	30.1	30.4	30.8	31.3
300	min	12.1	12.8	13.3	13.7	13.8	14.0	14.2
600	min	7.58	7.72	7.81	7.88	7.90	7.93	7.97
1200	min	4.13	4.20	4.25	4.30	4.32	4.34	4.36

Discharge Rates in Amperes to Various End Voltages at 25°C (77°F)

Time	End Voltage	1.85V	1.80V	1.75V	1.70V	1.67V	1.65V	1.60V
5	min	19.1	22.6	24.9	27.0	27.7	28.6	29.8
8	min	17.0	18.8	19.9	20.8	21.1	21.5	22.1
10	min	14.2	15.7	16.8	17.7	18.0	18.4	19.0
15	min	11.3	12.2	12.9	13.4	13.6	13.7	13.9
20	min	9.71	10.2	10.3	10.7	10.9	11.0	11.2
30	min	6.78	7.19	7.46	7.69	7.78	7.90	8.07
60	min	3.63	3.85	4.00	4.13	4.19	4.24	4.32
120	min	1.88	2.01	2.12	2.21	2.25	2.29	2.34
300	min	0.961	1.032	1.071	1.097	1.108	1.12	1.13
600	min	0.593	0.612	0.619	0.626	0.628	0.631	0.636
1200	min	0.319	0.327	0.332	0.337	0.339	0.341	0.343

All data on the spec. sheet is an average value:

The tolerance range : X<6min (+15%~-15%), 6min≤X<10min (+12%~-12%), 10min ≤X < 60min (+8%~-8%), X≥60min (+5%~-5%)